




AbraxSys
RUGGED LCD SOLUTIONS

12.1" Sunlight Readable High Brightness Industrial Grade VESA Mount Display Monitor

Model SRD-VM-121

Model SRD-VM-121 LCD monitor utilizes the latest 12.1" XGA (1024x768) TFT Flat Panels with Sunlight Readability Enhancements including (but not limited to) 1200 nits high-luminance LED backlighting and Ultra High Contrast Sun Readability 60:1 CR @10,000 Lux. AbraxSys has added a versatile Analog-Digital interface board, backlight inverter and OSD controls. All elements, including a toughened glass protective screen have been packaged in a compact, rugged metal housing. The result is a flexible Display Head, ready for integration as part of any system; as an analog monitor, or a touchscreen driven human-machine interface.

This industrial grade Sunlight Readable LCD TFT monitor is designed for use throughout a wide range of harsh outdoor applications. These rugged LCD displays are rigorously tested to ensure compliance with various industry standards and are engineered to withstand the effects of severe environments such as water, dust and dirt intrusion. These products perform well beyond ordinary 'commercial' type monitors. AbraxSys' high bright Sunlight Readable LCDs are ideal for use in any high ambient light condition, and will give you the intensity and brilliance your application requires.



 HDMI

 VGA

 DVI

 Display Port

Technical Specifications

General

Model:

SRD-VM-121

Display Size

12.1"

Display Type

Long-Life Industrial Grade Active Matrix TFT LCD

Backlight Technology

Solid State, Long-Life LED, with Light Source Redundancy

Optical Films Enhancements

Boosts efficiency of the backlight's light utilization and minimizes the surface reflection of ambient light. The result is a transmissive enhancement that features higher contrast and a wider range of colors, even in bright outdoor light, than traditional reflective LCDs.

Brightness

1200 nits (cd/m²)

Contrast Ratio

600:1

Aspect Ratio

4:3

Resolution

1024 x 768

Colors Supported

16.2M

Viewing Angles

-85° to 85° Horizontal

-85° to 85° Vertical

Video Inputs

DVI, HD15 (VGA), HDMI, DisplayPort

User Controls

Front Keypad (can also be configured for rear controls, or Manual Full-Range Dimming Turn Pot, Automatic Dimming Sensor, or Remote Dimming)

Protective Window

3mm Sparkle Free Front Protective Impact Window or Projected Capacitive Touch Screen

Power Types

90 VAC to 264 VAC; 12V DC; 24V DC; 9 to 36V DC; or 20 to 53V DC

Physical Attributes

Front Bezel

High Grade 6061T Aluminum, Electrochemical Anodized for added Corrosion Resistance, Black Textured Finish per Military Standards FED-STD-595

Panel Mounting

Pass Through or Rear Mount VESA

Rear Enclosure

High Grade 6061T Aluminum, Electrochemical Anodized for added Corrosion Resistance, Black Textured Finish per Military Standards FED-STD-595

Overall Dimensions

11.246 x 9.098 x 2.5 in
(285.64 x 231.08 x 63.50mm)

Weight

6 lbs (2.72 kg)

Sunlight Readability

The latest optical technology for high ambient light conditions

Warranty Period

3 Years

Environmental

Sunlight Readability

The latest optical technology for high ambient light conditions

Operating Temperature Range

-30°C to 85°C (-22°F to 185°F)

Storage Temperature

-40°C to 85°C (-40°F to 185°F)

Humidity

5% to 95% RH (non-condensing)

Shock

Operating: 30g's, 11ms, ½ Sine

Vibration

1g RMS 20-500Hz

Fasteners

Vibration-proof, self-locking, fastener system

EMI

FCC Class B pursuant to Part 15 of the FCC Rules

Agency Compliance

CE

Altitude

Operating 0 to 10,000 ft.
/ Storage 0 to 40,000 ft.

RoHS Compliant

Yes

Rating

NEMA 12 / IP50

Additional Add-On Options

Touch Screen Technology**Resistive****Hardened Armored Touch Technology****Power Type Choices**

90 VAC to 264 VAC; 12V DC; 24V DC; 9 to 36V DC; or 20 to 53V DC

Video Input Options


DVI, HD15 (VGA), HDMI, and/or DisplayPort

Conformal Coating of all Internal Circuit Boards**Extended Operational Temperature Ranges****Customization Services****Dimming Capabilities**

Standard, or Optional Full-Range Manual Turn-Pot, Automatic Dimming Sensor, Remote Dimming

Custom Video Modes**Private Labeling Services**

Mechanical Drawings



These technical and mechanical resources are subject to change without notice.



AbraxSys
RUGGED LCD SOLUTIONS

(800) 883-9050

info@abraxsyscorp.com

www.abraxsyscorp.com

6161 Keller's Church Road, Units 6151B, 6161A, 6161B, 6171A & 6171B
Pipersville, Pennsylvania 18947 U.S.A.